

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT

<b>NAME OF THE PRODUCT</b>	GOO HHS Priming spray for plastic and metal 400 ml
<b>CODE</b>	090150 (light grey) RAL 9002 090151 (grey) RAL 7040 090152 (dark grey) RAL 7021

## 2. DESCRIPTION

"GOO HHS" filler is a fast-drying primer suitable for the repair and rectification of small areas with anti-corrosion properties on the repaired area of the vehicle. Perfect adhesion on plastics as PC, PVC, ABS, PA, SAN, PU, UP, EP and metals such as iron, steel, zinc and aluminium. It can be painted with water-based paints or dissolvent based paints.

- High film thicknesses can be applied without sagging.
- Very high filling and opacity properties.
- Can be over coated with water and solvent based paints.
- Resistant to Anti Silicone wipes.
- Very fast drying.
- Easy to sand wet and dry

## 3. PHYSICAL PROPERTIES

Chemical base	Acrylic Resin
VOC content	271g/500ml
Coverage	1.2m <sup>2</sup>
Storage notes	3 years in appropriate storage (-10°C-25°C, relative air humidity of max.60%)

## 4. APPLICATION DATA

- Shake aerosol for at least two minutes, after agitator ball is free.
- Apply in cross coat from distance of 250 mm from object.
- 3 coats at 70-80 um
- Drying time: 60 minutes at 20°C
- IR: 15-20 min.
- After use turn aerosol upside down and empty valve.

## 5. DISPOSAL

Completely emptied cans should be put in recycling skips or appropriate containers. Cans which are not empty should be disposed of as special refuse.



**BOSSAUTO INNOVA, S.A.**  
Pol. Ind. Vallcristol / Thomas Edison 16,  
08430 La Roca del Vallés, Barcelona  
t: +34 938 604 923 / f: +34 938 712 336  
info@bossauto.com / [www.bossauto.com](http://www.bossauto.com)



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However, the data is not binding and without warranty.