

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Tint-plast tube 75ml anthracite
CODE	090028
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona)
PHONE	902 100 667
FAX	902 363 047
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

TINT-PLAST is a quick-drying plastic paint. It is used to treat and enhance coloured plastics, which have faded or lost their colour due to weathering. It is also highly suitable for changing a colour to a darker shade. Due to its long-lasting effects the treated surfaces are enhanced to the greatest extent. TINT-PLAST is resistant to car washes and abrasion.

3. TECHNICAL INFORMATION

Degree of lustre:	Silky
Drying and possibility working over:	Dry, warm air (DIN 50014, 23°C and 50% relative air humidity)
Film-forming temperature:	At least 7°C ambient and underground (does not work well in direct sunlight).
Physical property:	TINT-PLAST is not resistant to salt water and is not suitable for continued exposure to stagnant water.
Chemical property:	TINT-PLAST should not be mixed with other colours of a different make, otherwise the specific properties will no longer be achieved.
Coat thickness/dry film	40-50 µm
Storage:	Store in frost-proof place.
Health:	Harmful if swallowed. Keep out of reach of children.
Environment:	TINT-PLAST has little odour and is environmentally compatible.

4. APPLICATION

It can be used on fine-pored materials and surfaces of plastic and imitation leather, e.g. tops of convertibles, folding roofs, hardtops, seats, inside roof linings, rubber parts, bumpers, cockpits

and other covering. It can be used on the above-mentioned surfaces for hobbies and for household or professional purposes (e.g. caravans, planes and cars).

5. PROCEDURE

1. Surfaces to be treated must be cleaned in order to remove dirt, grease, residues and oil.
2. TINT-PLAST should be removed immediately after application from the parts or surfaces that do not need to be treated.
3. TINT-PLAST can be applied well with the soft side of a sponge. The sponge should be moistened before use. It is also possible to apply TINT-PLAST with ordinary anoint brush. However, whichever tool is used, it is important to ensure that TINT-PLAST is applied in very thin layers.
4. If the desired colour shade is not achieved at the first attempt, then it is possible to repeat the procedure 2 or 3 times after the first coat has dried.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.