

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf (7 Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	DSS Adhesive reinforcing mesh, 50mmx20m
CODE	090055
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona)
PHONE	902 100 667
FAX	902 363 047
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

DSS Adhesive reinforcing mesh is a fibre tape used to reinforce your plastic. It has its own adhesive backing to make it stick to any plastic. Available in 20 meters rolls (68 Foot Roll).

3. FEATURES

- Self-Adhesive.
- Inexpensive to use.
- Adds the necessary strength to the repair area.
- Allows filler to penetrate through tape for added strength.
- Easy to cut to the required size.

4. APPLICATION INSTRUCTIONS

- 1. Sand repair area with 80-120 grit sand paper.
- 2. Clean repair area with recommended cleaner (all plastic prep).
- 3. Cut tape to required lengths. Cut as many pieces as required.
- 4. Apply tape strips over rip, gouge, or bend to form replacement tab.

5. Apply thin coat of adhesive filler to tear repair area, or, liberally apply repair material for replacement tab.

6. Apply more adhesive fillers over tape as required for additional strength.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.