

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Fibreglass blanket
CODE	090087
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION AND CHARACTERISTICS

Fiberglass piece specially destined to repair metallic surfaces and other substrates. Available in bulk per m² (1m² = 125 x 80 cm / 300 g).

- Good wet-out in resin
- Multi-resin-compatible
- Good tensile with flexibility
- Highly soluble resin binder
- Excellent fiber distribution
- Uniform weight
- Excellent translucency

3. SPECIFICATIONS

Test Item	Unit	Standard
Area Weight	G/m ²	300±10%
Binder Content	%	4.0±0.9
Water Content	%	<0.2
Tensile Strength	MD N/150 mm	60
Tensile Strength	CD N/150 mm	60
Width	mm	
Permeation Rate	s	<30
Color	White, slightly yellow	

4. PACKING AND STORAGE

Each roll is packed in a plastic bag and is wrapped up in a sleeve. The fiberglass blanket should be stored in closed containers at temperature between -10C and 40C for no more than 12 months, and protected from frost and direct sunlight.



BOSSAUTO INNOVA, S.A.
Pol. Ind. Vallcristof C/ Thomas Edison 16,
08430 La Roca del Vallés, Barcelona
t: +34 938 604 923 / f: +34 938 712 336
info@bossauto.com/ www.bossauto.com



The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.