

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf C' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336

info@bossauto.com/ www.bossauto.com



# TECHNICAL DATA SHEET

#### 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE Special paint spray for plastic BOSS 500ml **PRODUCT** CODE 110025 (Black) 110026 (Grey Anthracite) **DISTRIBUTOR** BOSSAUTO INNOVA, S.A. ADDRESS c/ Thomas Edison 16, Apartado de correos 95 CITY 08430 La Roca del Vallés (Barcelona) **PHONE** 902 100 667 **FAX** 902 363 047 **E-MAIL** info@bossauto.com WEB www.bossauto.com

## 2. DESCRIPTION

Designed for coating of car parts made from synthetics, polyester and polycarbonate. Can be applied on plastic pumpers, outer mirrors, spoilers etc., returning to the more damage parts an incredible appearance. This spray for plastic protects the lower parts.

# Advantages:

- Easy application
- Good adhesion, high coverage
- Fast drying
- It does not contain heavy metals like cadmium or chromium

## 3. TECHNICAL DATA

Combination of nitro-alkyd resins.

#### 4. APPLICATION

A. Coat thickness after 2 crossways applications:

Approx. 20-30µm

**B.** Drying times

Dust dry: after approx.30 minutes Touch-dry: after approx. 1 hour Totally dry: after approx. 24 hours.

C. Can be repainted After 15 minutes.

1-2

Last review: 16/02/2016



## BOSSAUTO INNOVA, S.A.

Pol. Ind. Validoriolf O' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



# D. Attention

Do not spray on surfaces previously coated with synthetic resin substances as the original coat may lift.

# E. Sequence of coats

- 1. Plastic adhesion primer
- 2. Plastic spray

The technical information is given in good faith, but the user should assure him that the performance of the product is sufficient for this application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Bossauto Innova cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for own applications.