

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT

<b>NAME OF THE PRODUCT</b>	T1010 White grease + PTFE spray 400 ml
<b>CODE</b>	110012

## 2. DESCRIPTION

This acid and resin-free spray protects all chrome-plated parts on bikes, motorcycles, cars and boats. Prevents corrosion and rust. Suitable for protecting battery poles. Lubricates hinges, locks, seat rails and other mechanisms. Water resistant to 90°C.

## 3. APPLICATION

White Grease is a superior water and heat resistant lubricant for the long-term protection of bearings, axles, chains, hinges and all moving parts. This convenient non-drip grease has special anti-wear additives.

## 4. DIRECTIONS FOR USE

Shake well before use. Spraying distance: 20-30cm.

## 5. TECHNICAL INFORMATION

Colour	White to dark amber
Texture	Smooth
Thickening agent	Lithium complex soap
Dropping point (°C)	±290°C
NLGI - Class	1
Application temperature:	
Min (°C)	-30
Max (°C)	160
Penetration (mm/10)	
Unworked	310-340
Worked 60 x	325
Worked 100.000 x (%)	+10
Extreme pressure properties	
Four ball weld load (Kg) (Pass)	±300
Base oil specification	
Viscosity at 40°C (Cst)	±160
Viscosity at 100°C (Cst)	±15.5
Pour point (°C)	±-17
Flash point (°C)	±240

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.