

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

DESCRIPTION	High gloss clear coat spray 500 ml
CODE	110034
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	C/ Thomas Edison 16, apartado de correos 95
LOCATION	08430 La Roca del Vallés (Barcelona)
TEL	902 100 667
FAX	902 363 047
E-MAIL	info@bossauto.com
WEBSITE	www.bossauto.com

2. DESCRIPTION

Fast drying, high gloss product. Plainest processing and all-purpose clearcoat.

Basis of raw material	Acrylic resins
VOC value	692 g/l

3. FIELD OF APPLICATION

Recommended for: Quick coating and long-term sealing of repair paint jobs and new paint jobs.

Substrate: Solvent-based or waterborne basecoats.

4. PRE-TREATMENT



Surface should be free from dust and grease. Before application shake aerosol vigorously for 2 min, spray to test.

5. PROTECTION







Personal protection is required
 Respirator mask type A2/P2



Protective gloves, e.g. from latex or nitrile.

6. DIRECTIONS OF USE

Spray passes		2 - 3 = 30 - 40 µm flash-off time: 5 - 10 min
Drying		Dust-free: 10 min at 20°C (70°F) touch-free: 20 min at 20°C (70°F) ready for polishing: 12 h at 20°C (70°F)
		IR drying possible 7 min (short-wave drying)
Continue	Can be polished after 12 h at 20 °C (70 °F) with all commercial polishes.	
Finish		When work is finished, reverse aerosol and spray valve empty.
Disposal	The emptied aerosols are suitable for household collection.	

7. CHARACTERISTICS

Solid content	20% per weight
Coverage	Approx. 0.5 - 0.75 m ² / aerosol at approx. 30 - 40 µm dried film thickness
Degree of gloss	90 units (60° measuring geometry)
Shelf life	3 years / 20 °C (70 °F)
Remarks	For professional use only

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.