

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	L102 Aluminium wheel spray 400 ml
CODE	110021
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

L102 Aluminium Wheel Spray is a lacquer spray for metals, wood and hard-plastics. This product is quick drying by using a well selected solvent mixture and an acrylic resin. The surface gets a protective layer and a shiny new look. L102 Aluminium Wheel Spray is suitable for all kinds of materials such as wood, stone, glass, metal etc.

L102 Aluminium Wheel Spray can not be used on styropor or things that are heated above 100°C.

- Yield: 400 ml for 1-2m²
- Coverage: Dependent on the film thickness: 2 to 3 layers.
- Application: Free surface of rust, dirt; let it dry. Cover the parts which should not be painted. Shake the aerosol well before use during 2 till 3 minutes. Spray several thin layers from a distance of appr. 30 cm. Turn the aerosol up side down after use and spray till only gas is coming out.
- Overpaintable: After 5 minutes. After 30 minutes tack-free. Dry within 90 minutes.

3. TECHNICAL INFORMATION

Resin:	Acrylic resin.
Pigments:	Lead-free metal pigments
Solvents:	mixture of aromatic hydrocarbons and acetone
Recommended film thickness:	±75 micron wet, 15-20 micron dry.
Gloss:	±80, gloss measuring angle 60°
Density:	±0.7 kg/l
Particle size:	5-15 micron
Colour:	Silver
Thinner:	MIBK, Acetone
Flash point:	-60°C

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.