

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	U101 Universal matt black spray 400 ml.
CODE	110023
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION OF THE PRODUCT

U101 Universal Matt Black is a lacquer spray for metals, wood and hard-plastics. This product is quick drying by using a well selected solvent mixture and acrylic. The surface gets a protective layer and a completely new look.

- Yield: 400 ml for 1-2 m²
- Coverage: Dependent on the film thickness: 2 to 3 layers
- Application: Free surface of rust, dirt; let it dry. Cover the parts which should not be painted. Shake the aerosol well before use during 2 to 3 minutes. Spray several thin layers from a distance of appr. 30 cm. Turn the aerosol upside down after use and spray till only gas is coming out.
- Overpaintable: After 10 minutes. After 15 minutes tack-free. Dry within 30 minutes.

3. TECHNICAL INFORMATION

Resin	Acrylic resin
Pigments	Lead-free
Solvents	Xylene
PVC	7 V/V %
Solids	± 21 % (m/m)
Recommended film thickness	± 75 micron wet, 15-20 micron dry
Gloss	Matt: ± < 10
	Gloss measuring angle 60°
Density	± 0.711 Kg/l
Particle size	5-15 micron
Colour	Black
Thinner	DMK, IPA



BOSSAUTO INNOVA, S.A.
Pol. Ind. Vallcristof C/ Thomas Edison 16,
08430 La Roca del Vallés, Barcelona
t: +34 938 604 923 / f: +34 938 712 336
info@bossauto.com/ www.bossauto.com



"The information contained herein has been obtained as the result of testing and development work carried out by us. However, this product can be put to numerous uses under widely varying circumstances and conditions and accordingly we do not guarantee the accuracy of the contents of the statements contained herein, and in particular, we do not warrant that this product is suitable for any particular use. We shall not be liable in any way whatsoever to any person who relies upon the statements contained herein without taking sufficient steps to ensure in advance that the product is suitable for this particular purpose, production, conditions and/or use"