

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

<b>NAME OF THE PRODUCT</b>	Exhaust paste 170 g
<b>CODE</b>	110028
<b>DISTRIBUTOR</b>	BOSSAUTO INNOVA, S.A.
<b>ADDRESS</b>	c/ Thomas Edison 16, Apartado de correos 95
<b>CITY</b>	08430 La Roca del Vallés (Barcelona) SPAIN
<b>PHONE</b>	+ 34 93 860 49 23
<b>FAX</b>	+34 93 871 23 36
<b>E-MAIL</b>	<a href="mailto:info@bossauto.com">info@bossauto.com</a>
<b>WEB</b>	<a href="http://www.bossauto.com">www.bossauto.com</a>

## 2. PRODUCT DESCRIPTION

Exhaust fitting paste is used to seal the joints (plug connections) at the installation or substitution of exhaust parts.

## 3. PROPERTIES

Fast drying, past-like, excellent sealing, asbestos-free.  
 Colour: approx. grey Pantone 430

### A. Drying



Will be hardened by the heat of the exhaust.

### B. Application

- Remove rust and grease and clean the parts to be treated.
- Spread plenty of the paste before assembly on sockets and clamps.
- Assemble and fasten the parts of the exhaust.
- The fitting paste will be hardened after the assembly by the heat of the exhaust and the connections sealed.

All current safety regulations, national legislation and requirements established by professional associations have to be strictly observed for the usage of this product. All information contained herein is based on practical experience and is given in good faith. No warranty is impressed or implied as the use of the product is outside the control of the company. Users should determine the suitability of a product or system for their own particulars purposes.