

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	U303 Universal satin black spray 400 ml
CODE	110033
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. PRODCUT DESCRIPTION

Spray composed of a combination of satin pigments and clear coat imparting a silky appearance to the surface. Fast drying. Indicated for any finish on automotive parts, polyester and wood to achieve an original finish.

3. PRODUCT CHARACTERISTICS

Fast drying, good coverage, lasting gloss, non-fading and UV resistant, good surface hardness. Resistant to petrol, chemicals and weather influences, wear resistant and scratch free, excellent adhesion.

4. PHYSICAL AND CHEMICAL CHARACTERISTICS

Contents	400 ml
Base	Acrylic resin
Colour	Black
VOC-content	Approximately 91% w/w
Solid Content	Approximately 9% w/w
Coverage	1,5 to 2 m ²
Dust dry	After 5 to 10 minutes
Tack free	After 10 to 20 minutes
Hardened/re-sprayable	After 2 hours
Heat resistant	To 110°C

5. USAGE

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MoTip primer suitable for the surface. After drying, sand the base layer (grain 600).

Treat

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

6. SHELF LIFE

10 years in closed packaging and stored in good conditions.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.