

BOSSAUTO INNOVA, S.A.
Pol. Ind. Valldoriolf O' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com/



TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Undercoating spray gun
CODE	050070
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

New spray gun for external and internal coating applications. A careful market research has shown that it is becoming increasingly mare difficult to clean the spray instruments used for chemical coating products since they are getting more complex and sophisticated; in fact after use a normal spray gun has to be cleaned immediately so as not to risk the product drying out and so causing the inevitable obstruction of the nozzles that makes the spray gun unusable. The cleaning process itself takes up time and the use of solvents that considerably increase the costs of application.

The answer to this problem is the new undercoating spray gun (050070), which is equipped with a universal spray nozzle that can be thrown away with the empty can. However, if wished, the nozzle (made of solvent resisting materials) can be used again by immersed if in a small quantify of cleaning solvent; in the meantime one can continue working by using another clean nozzle on the spray gun. The cost of the nozzle however is much less than the cost of cleaning a normal spray gun and therefore if can be thrown away without hesitation. Provision has been made also for the quick connection to the nozzle of a special 1 metre long hose with a patented nozzle for the coating nebulization in boxes.

3. DIRECTIONS FOR USE











1-2



BOSSAUTO INNOVA, S.A.

Pol. Ind. Valldoriolf C' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/www.bossauto.com



- 1. Screw the hose on A/205 body
- 2. Screw A/205 body on the blow gun
- 3. Connect and screw the complete body on the fin
- 4. Connect the gun to the air line
- 5. Quick bayonet connection with nylon hose \emptyset 8 x 1000 and atomizing nozzle.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.

2-2