

Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE

NAME OF THE PRODUCT 2K HS "Anti-scratch" Acrylic clear coat 2:1

CODE 010002 5L 010007 1L

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Regulation (EC) No 1272/2008

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Hazardous to the aquatic environment, long-term hazard, Category 3, Aquatic Chronic 3:

H412.

Eye Irrit. 2: Eye irritation, Category 2, H319.

Flam. Liq. 3: Flammable liquids, Category 3, H226. Skin Irrit. 2: Skin irritation, Category 2, H315.

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317.

Specific target organ toxicity if swallowed, repeated exposure, Category STOT RE 2:

2, H373.

Specific toxicity causing drowsiness and dizziness, single exposure, STOT SE 3:

Category 3, H336.

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335.

2.2. Label elements

CLP Regulation (EC) No 1272/2008

Warning







Hazard statements

H412 - Harmful to aquatic life with long lasting effects. Aquatic Chronic 3:

Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

H373 - May cause damage to organs through prolonged or repeated exposure STOT RE 2:

(Oral).

STOT SE 3: H336 - May cause drowsiness or dizziness. STOT SE 3: H335 - May cause respiratory irritation.

This security data sheet replaces all the previous ones.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 Wear protective gloves/ protective clothing/ respiratory protection/

eye protection/ protective footwear.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use ABC powder extinguisher to extinguish.

P501 Dispose of the contents/containers in accordance with the current

legislation on waste treatment.

Supplementary information

Contains Hydroxyphenyl benzotriazol derivative.

Sustancias que contribuyen a la clasificación

N-butyl acetate; Xylene; Hydrocarbons, C9, aromatics; Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

2.3. Other hazards

Product contains PBT/vPvB substances: Octametilciclotetrasiloxano, Decametilciclopentasiloxano, Dodecametilciclohexasiloxano, Oxido de bis(tributilestano)

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1. Substance

Non-applicable.

3.2. Mixture

Chemical description:

Mixture composed of additives and resins in solvents.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/ Classification		Concentration
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29- XXXX	N- butyl acetate¹ Regulation 1272/2008 Flam. Liq. 3:H226 STOT SE 3: H336 EUH066 Warning	ATP CLP00	10 - <25%



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32- XXXX	Regulation 1272/2008 Acute Tox. 4: H312+H332 Aquatic Chronic 3: H412 Asp. Tox. 1: H304 Eye Irrit. 2: H319 Flam. Liq. 3: H226 Skin Irrit. 2: H315 STOT RE 2: H373 STOT SE 3: H335 Danger	Self-classified	10 - <25%
CAS: 64742-95-6 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35- XXXX	Hydrocarbons, C9, aromatics ² Regulation 1272/2008 Aquatic Chronic 2: H411 Asp. Tox. 1: H304 Flam. Liq. 3: H226 STOT SE 3: H335 STOT SE 3: H336 EUH066 Danger	Self-classified	2,5 - <5%
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29- XXXX	2-methoxy-1-methylethyl aceta Regulation 1272/2008 Flam. Liq. 3: H226 Warning	te¹ ATP ATP01	0,5 - <1%
CAS: Non-applicable EC: 400-830-7 Index: 607-176-00-3 REACH: 01-0000015075-76- XXXX	Hydroxyphenyl benzotriazol der Regulation 1272/2008 Aquatic Chronic 2: H411 Skin Sens. 1: H317 Warning	ATP CLP00	0,5 - <1%
CAS: 1065336-91-5 CE: 915-687-0 Index: Non-applicable REACH: 01-2119491304-40- XXXX	Reaction mass of Bis(1,2,2,6,6-4-piperidyl) sebacate and Methy pentamethyl-4-piperidyl sebacate Regulation 1272/2008 Aquatic Acute 1: H400 Aquatic Chronic 1: H410 Repr. 2: H361f Skin Sens. 1A: H317 Warning	yl 1,2,2,6,6-	<0,2-<0,25%

(1) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830.

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

4. FIRST AID MEASURES

4.1. Description of first aid measures

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/www.bossauto.com/



By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2. Most important symptoms and effects, both acute and delayed

Acute and delayed effects are indicated in sections 2 and 11.

4.3. Indication of any immediate medical attention and special treatment needed Non-applicable.

5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO^{c}).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2. Special hazards arising from the substance or mixture

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3. Advice for firefighters

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2. Environmental precautions

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3. Methods and material for containment and cleaning up

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4. Reference to other sections

See sections 8 and 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for storage

Minimum Temp.: 5°C

Maximum Temp.: 30°C

Maximum time: 24 Months

General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5.

7.3. Specific end use(s)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Control parameters

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational ex	xposure limits	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h) IOELV (Stel)	50 ppm 150 ppm	241 mg/m³ 723 mg/m³
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (8h) IOELV (Stel)	50 ppm 100 ppm	221 mg/m³ 442 mg/m³
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h) IOELV (Stel)	50ppm 100ppm	275 mg/m³ 550 mg/m³

DNEL (Workers)		Short exposure	е	Long exposure	
Identification		Systematic	Local	Systematic	Local
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Hydrocarbons, C9,	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
aromatics	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
CAS: 64742-95-6 EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	150 mg/m³	Non-applicable

This security data sheet replaces all the previous ones. Emission date: 10/09/2021 – Review date: 04/02/2022 www.bossauto.com



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



2-methoxy-1-	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
methylethyl acetate CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	550 mg/m ³	275 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
derivative	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
CAS: Non-applicable EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,35 mg/m ³	Non-applicable
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4-	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,68 mg/m ³	Non-applicable

DNEL (General popula	ation)	Short exposure		Long exposure	
Identification		Systematic	Local	Systematic	Local
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Xylene	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³
Hydrocarbons, C9,	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
aromatics CAS: 64742-95-6	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 918-668-5	Inhalation	Non-applicable	Non-applicable	32 mg/m ³	Non-applicable
2-methoxy-1-	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
methylethyl acetate CAS: 108-65-6	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
EC: 203-603-9	Inhalation	Non-applicable	Non-applicable	33 mg/m³	33 mg/m ³
Hydroxyphenyl	Oral	Non-applicable	Non-applicable	0,025 mg/kg	Non-applicable
benzotriazol derivative CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,085 mg/m ³	Non-applicable
Reaction mass of Bis (1,2,2,6,6-pentamethyl -4-piperidyl) sebacate	Oral	Non-applicable	Non-applicable	0,05 mg/kg	Non-applicable
and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
sebacate CAS: 1065336-91-5 EC: 915-687-0	Inhalation	Non-applicable	Non-applicable	0,17 mg/m³	Non-applicable

PNEC

Identification				
	STP	35,6 mg/L	Fresh water	0,18mg/L
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Soil	0,09 mg/Kg	Marine water	0,018mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981mg/Kg
	Oral	Non-applicable	Sediment (Marine water)	0,098mg/Kg



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



	STP	6,58mg/L	Fresh water	0,327mg/L
Xylene CAS: 1330-20-7	Soil	2,31mg/Kg	Marine water	0,327mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46mg/Kg
20. 213 333 7	Oral	Non-applicable	Sediment (Marine water)	12,46mg/Kg
2-methoxy-1-	STP	100mg/L	Fresh water	0,635mg/L
methylethyl acetate	Soil	0,29mg/Kg	Marine water	0,064mg/L
CAS: 108-65-6	Intermittent	6,35mg/L	Sediment (Fresh water)	3,29mg/Kg
EC: 203-603-9	Oral	Non-applicable	Sediment (Marine water)	0,329mg/Kg
Hydroxyphenyl	STP	10 mg/L	Fresh water	0,002 mg/L
benzotriazol derivative	Soil	2 mg/kg	Marine water	0 mg/L
CAS: Non-applicable	Intermittent	0,028 mg/L	Sediment (Fresh water)	3,37 mg/kg
EC: 400-830-7	Oral	Non-applicable	Sediment (Marine water)	0,337 mg/kg
Reaction mass of Bis (1,2,2,6,6-pentamethyl-	STP	1 mg/L	Fresh water	0,002 mg/L
4-piperidyl) sebacate and Methyl 1,2,2,6,6-	Soil	0,21 mg/kg	Marine water	0 mg/L
pentamethyl-4-piperidyl sebacate	Intermittent	0,009 mg/L	Sediment (Fresh water)	1,05 mg/kg
CAS: 1065336-91-5 EC: 915-687-0	Oral	Non-applicable	Sediment (Marine water)	0,11 mg/kg

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

Respiratory protection.

Mandatory respiratory tract protection.

Filter mask for gases, vapours and particles.

Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

EN 149:2001+A1:2009 EN 405:2002+A1:2010



Specific protection for the hands.

Mandatory hand protection.

Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: >480 min, Thickness: 0.062 mm). Replace the gloves at any sign of deterioration.

EN 420:2004+A1:2010



As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.





Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



	Ocular and facial protection. Mandatory face protection. Panoramic glasses against splash/projections. Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. EN 166:2002
	EN ISO 4007:2018
	Body protection. Mandatory complete body protection. Antistatic and fireproof protective clothing. Limited protection against flames. EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018
	Body protection. Mandatory foot protection. Safety footwear with antistatic and heat resistant properties. Replace boots at any sign of deterioration. EN ISO 13287:2013 EN ISO 20345:2011
+	Additional emergency measures. Emergency shower. ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011
**	Additional emergency measures. Eyewash stations. DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 49,98% weight

V.O.C. density at 20°C: 489,77 kg/m³ (489,77 g/L)

Average carbon number: 7,07

Average molecular weight 112,12 g/mol



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 515 kg/m³ (515 g/L)

EU limit for the product (Cat. B.E): 840 g/L (2010)
Components: (Organic diluent); (Hardener solvent)

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

For complete information see the product datasheet.

Appearance

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Solvent

Odour threshold: Non-applicable *

Volatility

Boiling point at atmospheric pressure: 133°C Vapour pressure at 20 °C: 947 Pa

Vapour pressure at 50 °C: 4892,02 Pa (4,89 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description

Density at 20 °C:

Relative density at 20 °C:

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Concentration:

Non-applicable *

pH: Non-applicable *
Vapour density at 20 °C: Non-applicable *
Partition coefficient n-octanol/water 20 °C: Non-applicable *
Solubility in water at 20 °C: Non-applicable *
Solubility properties: Immiscible

Decomposition temperature:

Melting point/freezing point:

Non-applicable *

Non-applicable *

Flammability

Flash Point: 26°C

Flammability (solid, gas):

Non-applicable *

Autoignition temperature: 315°C
Lower flammability limit: Not available
Upper flammability limit: Not available

Particle characteristics

Median equivalent diameter Non-applicable *

9.2. Other information

Information with regard to physical hazard classes

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

www.bossauto.com

^{*}Not relevant due to the nature of the product, not providing information property of its hazards.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Other safety characteristics

Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *

10. STABILITY AND REACTIVITY

10.1. Reactivity

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2. Chemical stability

Chemically stable under the conditions of storage, handling and use.

10.3. Possibility of hazardous reactions

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4. Conditions to avoid

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5. Incompatible materials

TOID! TIICOIIIPUCID	ic illaccitatio			
Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6. Hazardous decomposition products

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

The experimental information related to the toxicological properties of the product itself is not available.

Dangerous health implications

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/ Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

www.bossauto.com

^{*}Not relevant due to the nature of the product, not providing information property of its hazards.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/ Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Hydrocarbons, C9, aromatics (3); Xylene (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

Specific target organ toxicity (STOT) - single exposure:

- Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

Aspiration hazard:

- Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable.

Specific toxicology information on the substances:

pecific toxicology information on the substances.					
Identification	Acute toxicity		Genus		
N-butyl acetate	LD50 oral	12789 mg/kg	Rat		
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit		
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat		
Hydrocarbons, C9, aromatics	LD50 oral	3492 mg/kg	Rat		
CAS: 64742-95-6	LD50 dermal	3160 mg/kg	Rabbit		
EC: 918-668-5	LC50 inhalation	6193 mg/L (4 h)	Rat		



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4h) (ATEi)	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
Hydroxyphenyl benzotriazol derivative CAS:	LD50 oral	>2000 mg/kg	
Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 400-830-7	LC50 inhalation	>20 mg/L	
Reaction mass of Bis(1,2,2,6,6-pentamethy 4-piperidyl) sebacate and Methyl 1,2,2,6,6-	LD50 oral	3230 mg/kg	Rat
pentamethyl-4-piperidyl sebacate	LD50 dermal	>2000 mg/kg	
CAS: 1065336-91-5 EC: 915-687-0	LC50 inhalation	>20 mg/L	

Acute Toxicity Estimate (ATE mix):

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	4787,81 mg/kg (Calculation method)	0%
Inhalation	47,88 mg/L (4 h) (Calculation method)	0%

12. ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available.

12.1. Toxicity

Acute toxicity

Identification	Concentration		Species	Genus
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675mg/L (72h)	Scenedesmus subspicatus	Algae
Xylene	LC50	>10 - 100 (96 h)		Fish
CAS: 1330-20-7	EC50	>10 - 100 (48 h)		Crustacean
EC: 215-535-7	EC50	>10 - 100 (72 h)		Algae
Hydrocarbons, C9, aromatics	LC50	>1 - 10 (96 h)		Fish
CAS: 64742-95-6	EC50	>1 - 10 (48 h)		Crustacean
EC: 918-668-5	EC50	>1 - 10 (72 h)		Algae
2-methoxy-1-methylethyl	LC50	161 mg/L (96h)	Pimephales promelas	Fish
acetate CAS: 108-65-6	EC50	481 mg/L (48h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Non-applicable		
Hydroxyphenyl benzotriazol	LC50	>1-10 mg/L (96h)		Fish
derivative CAS: Non-applicable	EC50	>1-10 mg/L (48h)		Crustacean
EC: 400-830-7	EC50	>1-10 mg/L (72h)		Algae



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-	LC50	0,9 mg/L (96h)	Danio rerio	Fish
piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl 4-piperidyl sebacate	EC50	Non-applicable		
CAS: 1065336-91-5 EC: 915-687-0	EC50	1,7 mg/L (72h)	Desmodesmus subspicatus	Algae

Chronic toxicity:

chi one toxicity:				
Identification	Concentration		Concentration Species	
N-butyl acetate	NOEC	Non-applicable		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-	NOEC	Non-applicable		
4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	NOEC	1 mg/L	Daphnia magna	Crustacean

12.2. Persistence and degradability

12121 1 crosscence and degradability					
Identification	Degradability		Biodegradability		
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable	
CAS: 123-86-4	COD	Non-applicable	Period	5 days	
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %	
Xylene	BOD5	Non-applicable	Concentration	Non-applicable	
CAS: 1330-20-7	COD	Non-applicable	Period	28 days	
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %	
2-methoxy-1-methylethyl acetate	BOD5	Non-applicable	Concentration	785 mg/L	
CAS: 108-65-6 EC: 203-603-9	COD	Non-applicable	Period	8 days	
	BOD5/COD	Non-applicable	% Biodegradable	100 %	
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl)	BOD5	Non-applicable	Concentration	20 mg/L	
sebacate and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	COD	Non-applicable	Period	28 days	
CAS: 1065336-91-5 EC: 915-687-0	BOD5/COD	Non-applicable	% Biodegradable	38 %	

12.3. Bioaccumulative potencial

Identification	Bioaccumulation potential			
N-butyl acetate	BCF	4		
CAS: 123-86-4	POW Log	1,78		
EC: 204-658-1	Potential	Low		



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Xylene	BCF	9
CAS: 1330-20-7	POW Log	2,77
EC: 215-535-7	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	POW Log	0,43
EC: 203-603-9	Potential	Low

12.4. Mobility in soil

Identification	Absorption/ desorption		Volatility	
NI butul postate	Koc	Non-applicable	Henry	Non-applicable
N-butyl acetate CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25°C)	Moist soil	Non-applicable
Xylene CAS: 1330-20-7	Кос	202	Henry	524,86 Pa·m³/mol
	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
Reaction mass of Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and	Кос	204400	Henry	0E+0 Pa∙m³/mol
Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate CAS: 1065336-91-5 EC: 915-687-0	Conclusion	Inmobile	Dry soil	No
	Surface tension	Non-applicable	Moist soil	No

12.5. Results of PBT and vPvB assessment

Product contains PBT/vPvB substances: Octametilciclotetrasiloxano, Decametilciclopentasiloxano, Dodecametilciclohexasiloxano, Oxido de bis(tributilestano)

12.6. Other adverse effects

Not described.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage.

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Regulations related to waste management:


In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated.

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014.

14. TRANSPORT INFORMATION

Transport of dangerous goods by land

With regard to ADR 2021 and RID 2021:



Transport of dangerous goods by sea

With regard to IMDG 39-18

With regard to IMD	G 39-18	
	14.1 UN number	UN1263
	14.2 UN proper shipping name	PAINT
	14.3 Transport hazard class(es)	3
	Labels	3
	14.4 Packing group	III
	14.5 Marine pollutant	No
	14.6 Special precautions for user	
3	Special regulations	223, 955, 163, 367
~	EmS Codes	F-E, S-E
	Physico-Chemical properties	See section 9
	Limited quantities	5 L
	Segregation group	Non-applicable
	14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Non-applicable



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Transport of dangerous goods by air

With regard to IATA/ICAO 2021

With regard to 17117	y 16/18 2021	
	14.1 UN number	UN1263
	14.2 UN proper shipping name	PAINT
	14.3 Transport hazard class(es)	3
	Labels	3
3	14.4 Packing group	III
	14.5 Environmental hazards	No
	14.6 Special precautions for user	
	Physico-Chemical properties	See section 9
	14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Non-applicable

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable.

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable. Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable. Article 95, REGULATION (EU) No 528/2012: Non-applicable.

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable.

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0.1~% by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Other legislation:

The product could be affected by sectorial legislation.

15.2 Chemical safety assessment

The supplier has not carried out evaluation of chemical safety.

16. OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks:

Non-applicable.

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3.

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 Harmful in contact with skin or if inhaled.

Aquatic Acute 1: H400 Very toxic to aquatic life.

Aquatic Chronic 1: H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 Causes serious eye irritation. Flam. Liq. 3: H226 Flammable liquid and vapour. Repr. 2: H361f Suspected of damaging fertility.

Skin Irrit. 2: H315 Causes skin irritation.

Skin Sens. 1: H317 May cause an allergic skin reaction. Skin Sens. 1A: H317 May cause an allergic skin reaction.

STOT RE 2: H373 May cause damage to organs through prolonged or repeated exposure

(Oral).

STOT SE 3: H335 May cause respiratory irritation. STOT SE 3: H336 May cause drowsiness or dizziness.



Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



Classification procedure:

Aquatic Chronic 3: Calculation method. Skin Sens. 1A: Calculation method. STOT SE 3: Calculation method STOT SE 3: Calculation method. Skin Irrit. 2: Calculation method. STOT RE 2: Calculation method.

Flam. Liq. 3: Calculation method (2.6.4.3).

Eye Irrit. 2: Calculation method.

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road.

IMDG: International maritime dangerous goods code.

IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation.

COD: Chemical Oxygen Demand.

BOD5: 5day biochemical oxygen demand.

BCF: Bioconcentration factor.

LD50: Lethal Dose 50.

LC50: Lethal Concentration 50. EC50: Effective concentration 50.

LogPOW: Octanolwater partition coefficient. Koc: Partition coefficient of organic carbon.

UFI: unique formula identifier.

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.