

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT

**NAME OF THE PRODUCT** DS-40 Acrylic solvent normal 5L  
**CODE** 010013

## 2. DESCRIPTION

High grade acrylic solvent for mixing and thinning acrylic substances, paints, lacquers and primers.

## 3. AREA OF APPLICATION

\* Exclusive use in industrial facilities \*

Acrylic solvent specially formulated for the dilution of PUR 2K nature enamels for car repainting or industrial sector.

It is used in percentages of up to 25% depending on the type of enamel or equipment to be used. The use of this solvent provides extensibility and shine, does not lengthen drying and avoids defects such as boiled, veiled, orange peel, etc.

## 4. PHYSICAL PROPERTIES

Density at 20°C (g/cc)	0,900 ± 0,005
V.O.C. (g/l)	895
Point of inflammation	29°C Method: closed cup.
Type of product	Solvent
Colour	Transparent and colourless

## 5. COMPOSITION

Nature	Esters, aromatic hydrocarbons
--------	-------------------------------

## 6. STORAGE

Keep under cover in a cool and well-ventilated place avoiding direct sunlight. Temperatures between 5 and 30°C recommended.

### Can life:

At least 2 years since its manufacture.

After this time, consult the technical department.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However, the data is not binding and without warranty.