

BOSSAUTO INNOVA, S.A.U.

Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923



atencioncliente@bossauto.com/ www.bossauto.com

TECHNICAL DATA SHEET

Updating Date: 29/01/2024

Version: 4

(**)Indicates changes from the previous version

SECTION 1. IDENTIFICATION OF THE PRODUCT

1.1 Product identifier: Hardener UHS Fast (VOC)

Other forms of identification: 010045 (0,5L) 010051 (2,5L)

1.2 Details of the supplier of the technical data sheet: (See FDT headline).

1.3 Emergency telephone: 93 860 49 23 (8:00 - 17:30).

SECTION 2. DESCRIPTION

- UHS acrylic hardener for universal use and fast drying.
- Aliphatic property to prevent yellowing.
- Compatible with low VOC products such as paint, clear coat, primer.

SECTION 3. PRODUCT FEATURES

Mixing ratio:	2:1 by the volume.
Pot life:	Same as the clear coat it accompanies.
Shelf-life:	At least one year at 20°C and in unopened original packaging.

The technical information is based on our experience. We guarantee the quality of the product; however, as the conditions of use are not under our control, we cannot assume any responsibility for the results obtained.

Emission Date: 13/05/2014 Revision Date: 13/06/2022