

BOSSAUTO INNOVA, S.A.U. Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 atencioncliente@bossauto.com/ www.bossauto.com



TECHNICAL DATA SHEET

Updating Date: 29/01/2024 Version: 5 (**)Indicates changes from the previous version

SECTION 1. IDENTIFICATION OF THE PRODUCT

1.1 Product identifier: Other forms of identification: Hardener UHS Medium (VOC) 010046 (0,5L) 010050 (2,5L)

- 1.2 Details of the supplier of the technical data sheet: (See FDT headline).
- 1.3 Emergency telephone: 93 860 49 23 (8:00 17:30).

SECTION 2. DESCRIPTION

- UHS acrylic hardener for universal use and normal drying.
- Aliphatic property to prevent yellowing.
- Compatible with low VOC products such as paint, clear coat, primer.

SECTION 3. PRODUCT FEATURES

Mixing ratio:	2:1 by the volume.
Pot life:	Same as the clear coat it accompanies.
Shelf-life:	At least one year at 20°C and in unopened original packaging.

The technical information is based on our experience. We guarantee the quality of the product; however, as the conditions of use are not under our control, we cannot assume any responsibility for the results obtained.