

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	UHS Express activator for primer 1L
CODE	020023
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. APPLICATION FIELD

Aliphatic polyisocyanate based catalyst that does not turn yellow. It stands out because of its shade stability and weather resistance.

3. PHYSICAL CHARACTERISTICS

Supply viscosity (20°C)	11 – 15 seg. F4
Density (20°C, g/cc)	0,98 ± 0,03
V.O.C. (g/l)	542
Flash point	26°C. Method: closed cup.
Water contents	< 0,05%
Product type	Catalyser/hardener
Colour	Transparent and colourless

4. COMPOSITION

Nature	Aliphatic polyisocyanate
--------	--------------------------

5. USE

- As a guide, it can be used at < 15°C temperatures.
- Tightly close the recipients once the product has been used in order to avoid the entrance of air and, therefore, a reaction that will damage the product and its use.

6. STORAGE

Keep indoors in a well aired and fresh place, avoiding the direct exposition of the sunlight. We recommend temperatures from 5 to 30 °C.

- Duration of the product: At least 1 year since its fabrication. After this period, consult the technical department.
- Canning should not be stored outdoors or be exposed to dramatic temperature variations. Preserve from frost.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.