

#### **BOSSAUTO INNOVA, S.A.**

Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com / www.bossauto.com



# **TECHNICAL DATA SHEET**

## 1. IDENTIFICATION OF THE PRODUCT

NAME OF THE PRODUCT Protection film

**CODE** 040019 (34 cm x 25 Yds)

040020 (60 cm x 25 Yds) 040006 (90 cm x 25 Yds) 040007 (120 cm x 25 Yds) 040008 (180 cm x 25 Yds) 040021 (240 cm x 25 Yds)

040009 (360 cm x 25 Yds)

### 2. DESCRIPTION

It is a plastic roll with a 19 mm masking tape incorporated which is normally used to protect parts of the vehicle which we do not need to paint. It includes an outer corona-treatment to ensure proper paint adhesion to the plastic.

## 3. TAPE FEATURES

Test	Value	Tolerance	Method
Paper semi crepe	57 g/m2	5%	PS-QUA-16
Colour	Yellow		
Total weight (adhesive paper) g/m2.:	93	5%	PS-QUA-16
Thickness	0.12 mm	10%	AFERA 4006
Adhesion	2,2 N/cm	10%	AFERA 4001
Tensile strength	32 N/cm	10%	AFERA 4004
Elongation at break	10%	2%	AFERA 4005
Maximum resistance	80 °C	max	

## 4. FILM PROTECTOR FEATURES

Nominal density	0.946 g/cm <sup>3</sup>
Melting point	126 a 130 ℃
Ignition point, approx.	350 °C
Thickness	8 microns +/- 10%
External face treatment	50 dinas minimum

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However, the data is not binding and without warranty.