

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT

NAME OF THE PRODUCT	LOGO TRANS double-sided adhesive tape, 30 cm x 5 cm, (10 strips)
CODE	040065

2. DESCRIPTION

Double-sided adhesive tape totally transferring the glue only to the part in contact with it. Specially designed for attaching logos and emblems to the vehicle.

3. TECHNICAL CHARACTERISTICS OF TAPE

Aspect	Adhesive tape with transparent film on a silicon substrate with protection liner
Sizes	L300 mm x h60 mm (300 mm x 50 mm Adhesive surface only)
Thickness of adhesive film	0,04mm
Thickness of tape	0,127mm
Adhesion on steel	8,75N/10cm
Temperature resistance	Up to +180°C
Resistance after thermal cycle	OK after three cycles
Cold impact resistance	Passes after 10 impacts
Application temperature	+15°C - +35°C

4. APPLICATION

- Remove the emblem or logo from vehicle by cutting its original adhesive.
- Thoroughly clean the old foam on the logo with an anti-silicon product and wait until it is completely dry. With same product thoroughly clean the surface where the logo will be fixed.
- Remove the red liner from LOGO TRANS adhesive, place the logo with its back side in contact with the double-sided adhesive film and apply a uniform manual pressure.
- Raise the logo from the adhesive strip. Place the logo on vehicle surface and apply a uniform manual pressure all over the logo.

5. PACKAGING

LOGO TRANS adhesive is available in holders of 10 strips each.

6. STORAGE

LOGO TRANS adhesive stored in its original package, in a dry and well-ventilated place, at a temperature between +5°C and +35°C has a shelf life of 12 months from manufacturing date.

7. NOTE

The above information and our technical indications (both verbal and written or resulting from testing), in particular those that regard the applications and uses of our products, correspond to our best knowledge and experience; however, they do not constitute our warranty relative to final results or our responsibility deriving from any juridical relationship whatsoever.

In fact, considering the multiplicity of materials, supports, handling and storage conditions, as well as the conditions of production and utilization, the user, in function of his specific circumstances of use, must always preventively verify all the information and instructions reported above.

No assertion contained in this publication is to be considered authorization or suggestion to violate any industrial property rights of third parties.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However, the data is not binding and without warranty.