

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT

<b>NAME OF THE PRODUCT</b>	Roll of HDPE Blue film
<b>CODE</b>	040217 (4mx300m) 040218 (6mx150m)

## 2. DESCRIPTION

A high performance masking film with perfect resistance to high temperature and appropriate for wide area works. It's flexible and with corona treatment and also treated for static cling.

- Sticks to surface immediately.
- Flexible, suits the shape of car and does not tear.
- Transparent, can be cut in the exact size
- Treated backing for good paint adhesion.
- High temperature resistance up to 110°C
- High water resistance even with water base paint.

## 3. TECHNICAL DATA

<b>Material</b>	Polythylene
<b>Color</b>	Blue
<b>Static</b>	Static Cling
<b>Measures</b>	040217 4mx300m 040218 6mx150m
<b>Thickness</b>	040217 8 micres 040218 9 micres
<b>Corona Treatment</b>	44 Dine
<b>Temperature</b>	+10°C - 106 °C (Painting booth)

## 4. INDICATIONS FOR STORAGE AND APPLICATION

### ● Suggestions Application

Masking suitable for cars, trucks, buses, boats, etc.

Never use on wet surface.

Dispenser also available, easy to use for a single person.

### ● Storage

Store in normal conditions of 21° C (70 °F) in its original packaging.

For optimal results, the product must be used within 12 months after its manufacturing date.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.