

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT

NAME OF THE PRODUCT	SYMMETRIC
CODE	100591

2. DESCRIPTION

This masking tape has two symmetrical tape faces to protect the interior of the vehicle and the rubber of the different openings during the repainting process. These use speeds up the entire masking process and reduces the use of materials (weatherstripping, tape, plastic with tape, etc) improving the profitability of the workshop and saving the user time in the process of preparing the vehicle. Designed for masking seals on windows, doors, bonnets and boots.

3. TECHNICAL CHARACTERISTICS

Backing	Saturated crepe paper
Adhesive	Solvent borne rubber resin
Colour	Yellow
Total thickness	135µm
Adhesion	5 N/25mm
Tensile strength	38 N/cm
Elongation	9%
Temperature resistance	110°C
Water resistant	Yes

4. ADVANTAGES

- Reduces the use of masking materials.
- Speeds up masking process.
- Applicable on all movables areas of vehicle: doors, rubber doors, door seals, bonnet, boot, etc.
- Adhesion on sheet metal and glass.
- Total protection of the interior of the vehicle and of the rubber seals of the openings.
- Improved paint finish in the protected area.
- Supports drying with UV lamps.
- Pre-cut every 12 centimeters to facilitate application in curved areas.

5. STORAGE

Suggested storage in dry area away from direct sunlight, within 15°C and 25°C with 50% of humidity maximum.

The shelf life of the product is at least 1 year from the manufacturing date.

Note: We recommend testing material in relation to the required applications. The company reserves the right to improve or make specific changes and modifications.

6. PACKAGING

Rolls with 20 meters long and 8 centimeters wide, with pre-cut every 12 centimeters, presented in self-dispensing container.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.