

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT

**NAME OF THE PRODUCT** Filler FIBERPLAST Fibreglass 1,8 kg  
**REFERENCE** 070008

## 2. HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

#### Hazard pictograms



#### Signal word

Danger.

#### Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

#### Precautionary statements

##### Prevention:

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/ mist/ vapours.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

##### Response:

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

**Hazardous components which must be listed on the label**

Styrene.

**Additional Labelling**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/ mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Chemical nature:** Mixture contains Resin.

**Components:**

Identification	Classification	Concentration (%w/w)
<b>Styrene</b> CAS-No.: 100-42-5 EC-No.: 202-851-5 Index-No.: 601-026-00-0 Registration number: 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (Hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapor): 11,8 mg/l	>=10-<20
<b>Titanium dioxide</b> CAS-No.: 13463-67-7 EC-No.: 236-675-5 Index-No.: Registration number: 01-2119489379-17	Carc. 2; H351	>=0,1-<1

<p><b>1,4-naphthoquinone</b>          CAS- No.: 103-15-4          EC-No.: 204-977-6          Index-No.:          Registration number: 01-2120760462-57</p>	<p>Acute Tox. 3; H301          Acute Tox. 1; H330          Skin Corr. 1C; H314          Eye Dam. 1; H318          Skin Sens. 1; H317          STOT SE 3; H335 (Respiratory system)          Aquatic Acute 1; H400          Aquatic Chronic 1; H410          M-Factor (Acute aquatic toxicity): 10          M-Factor (Chronic aquatic toxicity): 1          Acute toxicity estimate          Acute oral toxicity: 124 mg/kg          Acute inhalation toxicity (dust/mist): 0,046 mg/l</p>	<p>&gt;=0.0025-&lt;0.025</p>
--	---	------------------------------

#### Substances with a workplace exposure limit

<p><b>Talc</b>          CAS-No.: 14807-96-6          EC-No.: 238-877-9          Index-No.:          Registration number:</p>		<p>&gt;=30-&lt;50</p>
--	--	-----------------------

For explanation of abbreviations see section 16.

## 4. FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General advice

In the case of accident or if you feel unwell, seek medical advice immediately.  
 Move out of dangerous area.  
 Take off contaminated clothing and shoes immediately.  
 Do not leave the victim unattended.  
 Symptoms of poisoning may appear several hours later.  
 Show this safety data sheet to the doctor in attendance.

#### Protection of first-aiders

First Aid responders should pay attention to self-protection and use the recommended protective clothing.

#### If inhaled

Move to fresh air.  
 Keep patient warm and at rest.  
 If breathing is irregular or stopped, administer artificial respiration.  
 Call a physician immediately.

#### In case of skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
 Call a physician if irritation develops or persists.

#### In case of eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
 Keep eye wide open while rinsing.  
 If easy to do, remove contact lens, if worn.  
 Consult a physician.

#### **If swallowed**

Rinse mouth with water.  
Do NOT induce vomiting.  
Call a physician immediately.

#### **4.2. Most important symptoms and effects, both acute and delayed**

##### **Risks**

Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging the unborn child.  
Causes damage to organs through prolonged or repeated exposure.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

##### **Treatment**

Treat symptomatically.  
Keep under medical supervision for at least 48 hours.

### **5. FIREFIGHTING MEASURES**

---

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>).  
Dry powder.  
Water spray jet.  
Alcohol-resistant foam.

##### **Unsuitable extinguishing media**

High volume water jet.

#### **5.2. Special hazards arising from the substance or mixture**

##### **Specific hazards during firefighting**

Build-up of dangerous/ toxic fumes possible in cases of fire/ high temperature.

##### **Hazardous combustion products**

Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### **5.3. Advice for firefighters**

##### **Special protective equipment for firefighters**

In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

##### **Further information**

Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately.  
This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## 6. ACCIDENTAL RELEASE MEASURES

---

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
Sweep up to prevent slipping hazard.  
In the case of vapour formation use a respirator with an approved filter.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

### 6.4. Reference to other sections

For personal protection see section 8.  
For disposal considerations see section 13.

## 7. HANDLING AND STORAGE

---

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.  
Avoid contact with skin and eyes.  
Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture.  
Avoid inhalation of dust from sanding.

#### Advice on protection against fire and explosion

Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage areas and containers

Store in original container.  
Keep containers tightly closed in a dry, cool and well-ventilated place.

#### Further information on storage conditions

Keep away from heat and sources of ignition.  
Protect from moisture.  
Keep away from direct sunlight.  
Do not store at temperatures above 30°C/ 86°F.

#### Advice on common storage

Incompatible with oxidizing agents.  
Keep away from food and drink.

**Storage class (TRGS 510)**

3.

**7.3. Specific end use(s)**

No data available.

**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational Exposure Limits**

Identification	Value type (Form of exposure)	Control parameters	Basis
Talc CAS-No.: 14807-96-6	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
	TWA (Respirable dust)	0,1 mg/m <sup>3</sup>	2004/37/EC
Further information: Carcinogens or mutagens			
Barium sulphate CAS-No.: 7727-43-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Styrene CAS-No.: 100-42-5	AGW	20 ppm - 86 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Titanium dioxide CAS-No.: 13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)		
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
	AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)		
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

**Biological occupational exposure limits**

Identification	Control parameters	Sampling time	Basis
Styrene CAS-No.: 100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g Creatinine (Urine)	In case of longterm exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No.1907/2006

#### Workers

Identification	Exposure routes	Potential health effects	Value
Styrene	Dermal	Long-term systemic effects, Chronic effects	406 mg/kg bw/day
	Inhalation	Long-term systemic effects, Chronic effects	85 mg/m <sup>3</sup>
	Inhalation	Acute systemic effects, Chronic effects	289 mg/m <sup>3</sup>
	Inhalation	Acute local effects, Short-term exposure	306 mg/m <sup>3</sup>

### Derived No Effect Level (DNEL) according to Regulation (EC) No.1907/2006

#### Consumers




Identification	Exposure routes	Potential health effects	Value
Styrene	Oral	Long-term systemic effects, Chronic effects	2,1 mg/kg bw/day
	Dermal	Long-term systemic effects, Chronic effects	343 mg/kg bw/day
	Inhalation	Long-term systemic effects, Chronic effects	10,0 mg/m <sup>3</sup>
	Inhalation	Acute systemic effects, Short-term exposure	174,25 mg/m <sup>3</sup>
	Inhalation	Acute local effects, Short-term exposure	182,75 mg/m <sup>3</sup>


### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Identification	Environmental Compartment	Value
Styrene	Fresh water	0,028 mg/l
	Marine water	0,014 mg/l
	Fresh water sediment	0,614 mg/kg dry weight (d.w.)
	Marine sediment	0,307 mg/kg dry weight (d.w.)
	Soil	0,2 mg/kg dry weight (d.w.)
	Sewage treatment plant	5 mg/l

## 8.2. Exposure controls

### Personal protective equipment

	<p><b>Eye protection</b>            Safety glasses with side-shields conforming to EN166.</p>
	<p><b>Hand protection</b>            Material: Fluorinated rubber.            Break through time: &gt;480 min.            Glove thickness: &gt;=0.4 mm.            Directive: DIN EN 374.            Protective index: Class 6.            Remarks: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection. Butyl gloves are not suitable. Nitrile gloves are not suitable. Avoid natural rubber gloves.</p>
	<p><b>Skin and body protection</b>            Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres. Long sleeved clothing.</p>

	<p><b>Respiratory protection</b>          Apply technical measures to comply with the occupational exposure limits.          If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.          Dry sanding, flame cutting and/or welding of the cured material will give rise to dust and/or hazardous fumes. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).          Filter type: Combined particulates and organic vapour type (A-P).</p>
---	--

### Protective measures

Ensure that eye flushing systems and safety showers are located close to the working place.  
 Avoid contact with the skin and the eyes.  
 Use only with adequate ventilation.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical state	Paste
Colour	Gray
Odour	Characteristic
Melting point/ range	-30°C Literary value styrene
Boiling point/ boiling range	145°C (1,013 hPa) Literary value styrene
Upper explosion limit/ Upper flammability limit	6,1% (V) Literary value styrene
Lower explosion limit/ Lower flammability limit	1,1% (V) Literary value styrene
Flash point	31°C (1,013 hPa) Literary value styrene
Ignition temperature	490°C (1,013 hPa) Literary value styrene
pH	Not applicable substance/mixture is non-soluble (in water)
Viscosity, dynamic	Not determined
Viscosity, kinematic	Not determined
Water solubility	0.32 g/l Literary value styrene (25°C)
Partition coefficient: noctanol/ water	No data available
Vapour pressure	6.67 hPa (20°C) Literary value styrene
Density	ca. 1.8 g/cm <sup>3</sup> (20°C)

### 9.2. Other information

Explosives	Not explosive In use, may form flammable/explosive vapour-air mixture
Self-ignition	Not auto-flammable

## 10. STABILITY AND REACTIVITY

### 10.1. Reactivity

No decomposition if used as directed.

### 10.2. Chemical stability

No decomposition if stored and applied as directed.



### 10.3. Possibility of hazardous reactions

#### Hazardous reactions

Avoid radical-forming starting agents, peroxides and reactive metals.

Polymerization can occur. Polymerization is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

### 10.4. Conditions to avoid

Heat, flames and sparks.

Strong sunlight for prolonged periods.

### 10.5. Incompatible materials

#### Materials to avoid

Strong acids and oxidizing agents polymerisation initiators.

Copper.

Copper alloys.

Brass.

### 10.6. Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

## 11. TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product

Acute inhalation toxicity: Acute toxicity estimate: >20 mg/l.  
 Exposure time: 4h.  
 Test atmosphere: vapour.  
 Method: Calculation method.

#### Components

Styrene	Acute oral toxicity	LD50 Oral (Rat): 5,000 mg/kg
	Acute inhalation toxicity	LC50 (Rat): 11,8 mg/l Exposure time: 4h Test atmosphere: vapour Acute toxicity estimate: 11,8 mg/l Test atmosphere: vapor Method: Calculation method
	Acute dermal toxicity	LD50 Dermal (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402
Titanium dioxide	Acute oral toxicity	LD50 Oral (Rat): > 5.000 mg/kg
	Acute inhalation toxicity	LD50 (Rat): >6,8 mg/l Exposure time: 4h

1,4-naphthoquinone	Acute oral toxicity	DL50 Oral (Rata): 124 mg/kg Acute toxicity estimate: 124 mg/kg Method: Calculation method
	Acute inhalation toxicity	LC50 (Rat): 0,046 mg/l Exposure time: 4h Test atmosphere: dust/mist Method: OECD Test Guideline 403  Acute toxicity estimate: 0,046 mg/l Test atmosphere: dust/mist Method: Calculation method
	Acute dermal toxicity	Assessment: The substance or mixture has no acute dermal toxicity. Effects of skin contacts may include: Causes burns.
Talc	Acute inhalation toxicity	Assessment: The substance or mixture has no acute inhalation toxicity

### Skin corrosion/irritation

Causes skin irritation.

#### Components

Styrene	Species: Rabbit. Result: irritating.
Titanium dioxide	Remarks: No skin irritation.
1,4-naphthoquinone	Result: Causes burns.

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components

Styrene	Species: Rabbit. Result: irritating.
Titanium dioxide	Remarks: Dust contact with the eyes can lead to mechanical irritation.
1,4-naphthoquinone	Result: Risk of serious damage to eyes.

### Skin sensitisation

Not classified based on available information.

### Respiratory sensitisation

Not classified based on available information.

#### Components

Styrene	Species: Guinea pig. Result: Does not cause skin sensitisation.
Titanium dioxide	Remarks: No known sensitising effect.
1,4-naphthoquinone	Result: May cause sensitisation by skin contact.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Suspected of damaging the unborn child.

#### Components

Styrene	Reproductive toxicity - Assessment: Suspected of damaging the unborn child. Some evidence of adverse effects on development, based on animal experiments.
---------	--

### STOT - single exposure

Not classified based on available information.

#### Components

Styrene	Assessment: May cause respiratory irritation
1,4-naphthoquinone	Assessment: May cause respiratory irritation

### STOT - repeated exposure

Causes damage to organs (ear) through prolonged or repeated exposure if inhaled.

#### Components

Styrene	Exposure routes: Inhalation. Target Organs: hearing organs. Assessment: Causes damage to organs through prolonged or repeated exposure.
---------	---

### Aspiration toxicity

Not classified based on available information.

#### Components

Styrene	May be fatal if swallowed and enters airways.
---------	---

## 11.2. Information on other hazards

### Endocrine disrupting properties

#### Product

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12. ECOLOGICAL INFORMATION

### 12.1. Toxicity

Styrene	Toxicity to fish	LC50 (Pimephales promelas (fathead minnow)): 4,02 mg/l Exposure time: 96h
	Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 4,7 mg/l Exposure time: 48h Method: OECD Test Guideline 202
	Toxicity to algae/aquatic plants	EC50 (Selenastrum capricornutum (green algae)): 4,9 mg/l Exposure time: 72h
		EC10 (Selenastrum capricornutum (green algae)): 0,28 mg/l Exposure time: 96h
	Toxicity to microorganisms	EC50 (Natural microorganism): ca. 500 mg/l Method: OECD Test Guideline 209
	Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 1,01 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211
	<b>Ecotoxicology Assessment</b> Chronic aquatic toxicity	Harmful to aquatic life with long lasting effects
Titanium dioxide	Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 1.000 mg/l Exposure time: 48h

1,4-naphthoquinone	Toxicity to fish	(Oryzias latipes (Japanese medaka)): 0,045 mg/l Exposure time: 96h Method: OECD Test Guideline 203
	Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 0,0261 mg/l Exposure time: 48h Method: OECD Test Guideline 202
	Toxicity to algae/aquatic plants	EC50 (Pseudokirchneriella subcapitata (algae)): 0,42 mg/l Exposure time: 72h
	M-Factor (Acute aquatic toxicity)	10
	M-Factor (Chronic aquatic toxicity)	1
	<b>Ecotoxicology Assessment</b> Acute aquatic toxicity	Very toxic to aquatic life
	<b>Ecotoxicology Assessment</b> Chronic aquatic toxicity	Very toxic to aquatic life with long lasting effects

### 12.2. Persistence and degradability

Identification	Biodegradability
Styrene	Result: Readily biodegradable. Biodegradation: 70,9% Exposure time: 28 d
1,4-naphthoquinone	Result: Not rapidly biodegradable Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301

### 12.3. Bioaccumulative potential

Identification	Partition coefficient: n-octanol/ water
Styrene	log Pow: 2,96 (25°C)
1,4-naphthoquinone	log Pow: 1,77 (25°C)

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

Assessment: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6. Endocrine disrupting properties

Assessment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7. Other adverse effects

Additional ecological information: No data available.

## 13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Product

Do not dispose of with domestic refuse.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Dispose of in accordance with local regulations.  
 Dispose of wastes in an approved waste disposal facility.  
 Send to a licensed waste management company.

### Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Store containers and offer for recycling of material when in accordance with the local regulations.  
 Packaging that is not properly emptied must be disposed of as the unused product.  
 Dispose of in accordance with local regulations.

### Waste Code

The following Waste Codes are only suggestions: 07 02 08, other still bottoms and reaction residues.

## 14. TRANSPORT INFORMATION

### ADN

14.1 UN number or ID number	UN 1866
14.2 UN proper shipping name	RESIN SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
14.5 Environmental hazards	
Environmentally hazardous	No
14.6 Special precautions for user	The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations
14.7 Maritime transport in bulk according to IMO instruments	Not applicable for product as supplied

### ADR

14.1 UN number or ID number	UN 1866
14.2 UN proper shipping name	RESIN SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)
14.5 Environmental hazards	
Environmentally hazardous	No

14.6 Special precautions for user	The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations
14.7 Maritime transport in bulk according to IMO instruments	Not applicable for product as supplied

#### RID

14.1 UN number or ID number	UN 1866
14.2 UN proper shipping name	RESIN SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
14.5 Environmental hazards	
Environmentally hazardous	No
14.6 Special precautions for user	The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations
14.7 Maritime transport in bulk according to IMO instruments	Not applicable for product as supplied

#### IMDG

14.1 UN number or ID number	UN 1866
14.2 UN proper shipping name	RESIN SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group	
Packing group	III
Labels	3
EmS Code	F-E, S-E
14.5 Environmental hazards	
Marine pollutant	No
14.6 Special precautions for user	The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations
14.7 Maritime transport in bulk according to IMO instruments	Not applicable for product as supplied

## IATA

14.1 UN number or ID number	UN 1866
14.2 UN proper shipping name	RESIN SOLUTION
14.3 Transport hazard class(es)	3
14.4 Packing group (Cargo)	
Packing instruction (cargo aircraft)	366
Packing instruction (LQ)	Y344
Packing group	III
Labels	Class 3 – Flammable liquids
14.4 Packing group (Passenger)	
Packing instruction (passenger aircraft)	355
Packing instruction (LQ)	Y344
Packing group	III
Labels	Class 3 – Flammable liquids
14.5 Environmental hazards	
14.6 Special precautions for user	The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations
14.7 Maritime transport in bulk according to IMO instruments	Not applicable for product as supplied

## 15. REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/ legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	Conditions of restriction for the following entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59)	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances	P5c FLAMMABLE LIQUIDS
Water hazard class (Germany)	WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2)
Volatile organic compounds	Directive 2004/42/EC Volatile organic compounds (VOC) content: < 250 g/l VOC content for the product in a ready to use condition

### Other regulations

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## 16. OTHER INFORMATION

---

### Full text of H-Statements

H226:	Flammable liquid and vapour.
H301:	Toxic if swallowed.
H304:	May be fatal if swallowed and enters airways.
H314:	Causes severe skin burns and eye damage.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H319:	Causes serious eye irritation.
H330:	Fatal if inhaled.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H361d:	Suspected of damaging the unborn child.
H372:	Causes damage to organs through prolonged or repeated exposure.
H400:	Very toxic to aquatic life.
H410:	Very toxic to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.: Acute toxicity.  
Aquatic Acute: Short-term (acute) aquatic hazard.  
Aquatic Chronic: Long-term (chronic) aquatic hazard.  
Asp. Tox.: Aspiration hazard.  
Carc.: Carcinogenicity  
Eye Dam.: Serious eye damage.  
Eye Irrit.: Eye irritation.  
Flam. Liq.: Flammable liquids.  
Repr.: Reproductive toxicity.  
Skin Corr.: Skin corrosion.  
Skin Irrit.: Skin irritation.  
Skin Sens.: Skin sensitisation.  
STOT RE: Specific target organ toxicity - repeated exposure.  
STOT SE: Specific target organ toxicity - single exposure.  
2004/37/EC: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work.  
DE TRGS 900: Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903: c - Biological limit values.  
2004/37/EC/TWA: Long term exposure limit.  
DE TRGS 900/AGW: Time Weighted Average.



ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AIIC - Australian Inventory of Industrial Chemicals.  
ASTM - American Society for the Testing of Materials.  
Bw - Body weight.  
CLP - Classification Labelling Packaging Regulation.  
Regulation (EC) No 1272/2008.  
CMR - Carcinogen, Mutagen or Reproductive Toxicant.  
DIN - Standard of the German Institute for Standardisation.  
DSL - Domestic Substances List (Canada).  
ECHA - European Chemicals Agency.  
EC-Number - European Community number.  
ECx - Concentration associated with x% response.  
ELx - Loading rate associated with x% response.  
EmS - Emergency Schedule.  
ENCS - Existing and New Chemical Substances (Japan).  
ErCx - Concentration associated with x% growth rate response.  
GHS - Globally Harmonized System.  
GLP - Good Laboratory Practice.  
IARC - International Agency for Research on Cancer.  
IATA - International Air Transport Association.  
IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk.  
IC50 - Half maximal inhibitory concentration.  
ICAO - International Civil Aviation Organization.  
IECSC - Inventory of Existing Chemical Substances in China.  
IMDG - International Maritime Dangerous Goods.  
IMO - International Maritime Organization.  
ISHL - Industrial Safety and Health Law (Japan).  
ISO - International Organisation for Standardization.  
KECI - Korea Existing Chemicals Inventory.  
LC50 - Lethal Concentration to 50 % of a test population.  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose).  
MARPOL - International Convention for the Prevention of Pollution from Ships.  
N.o.s. - Not Otherwise Specified.  
NO(A)EC - No Observed (Adverse) Effect Concentration.  
NO(A)EL - No Observed (Adverse) Effect Level.  
NOELR - No Observable Effect Loading Rate.  
NZIoC - New Zealand Inventory of Chemicals.  
OECD - Organization for Economic Co-operation and Development.  
OPPTS - Office of Chemical Safety and Pollution Prevention.  
PBT - Persistent, Bioaccumulative and Toxic substance.  
PICCS - Philippines Inventory of Chemicals and Chemical Substances.  
(Q)SAR - (Quantitative) Structure Activity Relationship.  
REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.  
SADT - Self-Accelerating Decomposition Temperature.  
SDS - Safety Data Sheet.  
SVHC - Substance of Very High Concern.  
TCSI - Taiwan Chemical Substance Inventory.  
TRGS - Technical Rule for Hazardous Substances.  
TSCA - Toxic Substances Control Act (United States).  
UN - United Nations.  
vPvB - Very Persistent and Very Bioaccumulative.

### Further information

Classification of the mixture		Classification procedure
Flam. Liq. 3	H226	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Repr. 2	H361d	Calculation method
STOT RE 1	H372	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.