

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT

NAME OF THE PRODUCT Filler for plastics 800 g
CODE 090014

2. DESCRIPTION

Filler for plastics Bossauto is elastic contour putty especially developed for use to coatable plastic parts. Excellent adhesive, high elasticity, fast dry and easy to sand.

3. TECHNICAL INFORMATION

Colour shade	Dark grey (approx. RAL 7024)
Mixing ratio	100:2
Hardener	Hardener (Peroxides)
Pot life	4-5 minutes
Dry: Object Temp. 20°C	The surface could be sanded after approx. 20-30 min.

Remarks

The substrate has to be clean, dry and free of grease. Abrade the surface. Remove all traces of old coats, which are not in good condition and firmly adhering. Do not apply on thermoplastic or acid containing ground coats (Reaktionsprimer). It is recommended to mix the filler with the hardener properly. Apply within appropriate temperature range (not less than +10°C object).

Marking	VbF	Hazardous material regulation
Bossauto Putty	n/a	Inflammable, Xn harmful, contains styrene
Hardener P	n/a	Xi irritating, oxidizing, contains benzoyl-peroxid

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your environment.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.