

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf C' Thomas Edison 16,

08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Aquapel marine water repellent blister pack
CODE	100901
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

Aquapel Marine is a treatment water repellent specifically for marine sports and for the aviation industry. Now available for marine industry. The formula used in Aquapel Marine glass treatment is applied to the exterior of marine glass, leaving the windshield and other treated glass surfaces water resistant. Controls salt water residue. Eliminates or reduces hard water marks. Forms a chemical bond to glass.

3. PROPERTIES

Aquapel Marine remarkably improves visibility in the rain. Makes rain bead up and roll right off. Makes it easier to remove ice, snow, bugs and dirt. Lasts for mmonths, up to six times longer than other leading glass treatments. Aquapel improves the visibility and the security in driving.

4. ADVANTAGES

- Improves remarkably visibility in rain; on the day and night.
- Repellent to rain and other adverse conditions such as snow.
- Easy to clean insects, dust, ice and snow.
- Lasts for months, up to six times longer than other leading glass treatments.

5. USE

- 1. Clean; thoroughly clean and dry the glass.
- 2. Apply; Hold the applicator between the thumb and fingers with the pad down and level over the windshield. Squeeze the wings together until a popping sound is heard and liquid is released onto the pad. Use immediately. Wipe the soft pad of the applicator over the glass up and down then side to side to ensure the glass is well covered. Avoid painted surfaces. Removes liquid from non-glass surfaces with dry paper towel.

1-2



BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf O' Thomas Edison 16,

08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com/



2-2

3. Dry; Wipe the glass with a clean dry paper towel immediately after Aquapel has been applied to the entire windshield. Dispose of applicator and paper towel. Failure to wipe immediately may cause hazing that requires additional buffing with a clean dry paper towel.

Notes:

- One single-use applicator will treat one windshield or two side Windows.
- Do not let Aquapel air dry onto windshield.
- When applying to large surface areas treat and dry one half at a time.

Conditions of application:

- Do not use in temperatures colder than 50°F or hotter than 90°F or in excessively humid conditions.
- One applied, Aquapel Glass Treatment can be reapplied as hended.
- Clearing glass with ordinary glass cleaners will not affect product durability.

6. PREVENTION OF HEALTH RISKS

A. Danger

- Combustible. Harmful or fatal if swallowed.
- Eye and skin irritant.
- Harmful if inhaled.

B. Remarks

- Keep away from heat, sparks, flames and other ignition sources.
- Do not smoke.
- Use only with adequate ventilation.
- International misuse by concentrating and inhaling the contents can be harmful or fatal.
- Avoid eye and skin contact.

7. FIRST AID MEASURES

- For eye or skin contact, wash thoroughly with water.
- In case of ingestion, eye/skin irritation or breathing is difficult, contact physician immediately.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.

This technical data sheet replaces the previous ones. Last review: 24/11/2015