

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	MATCHPEN colour light
CÓDE	050131
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona)
PHONE	902 100 667
FAX	902 363 047
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

BOSSAUTO presents a portable lamp designed for work and perfect for the identification of color variable tonalities, for identifying whether the silver pigmentation is thin or thick and equalize the colors. Plus, it is perfect for checking the coverage, looking over the damaged areas of the vehicle, identifying the defects during the painting process, etc.

Colourmatch is the first range of work lights for colour match and detailing in the world. The special LED with high CRI value is for perfect colour recognition. It is perfect for any paint, polish, cleaning or prep-zone operation and is the only colour match work light range in the world. The sturdy Colourmatch products are designed for use in the painting workshop. They are supplied with a replaceable glass lens resistant to all kind of solvents and tolerating daily cleaning. It increases the quality and finish of each operation and reduce the rate of time-consuming and costly re-work.

MATCHPEN is a small penlight easy to carry and always at hand in the pocket. The light output is very powerful with excellent colour recognition properties. MATCHPEN is with focus function for concentrated and focused light beam ranging from 10° to 70°. 2xAAA batteries are included.

3. MAIN CHARACTERISTICS

Light source	Ultra-high CRI LED
Luminous flux	100 lm
Operating time	2h
Ingress protection	IP54
CRI	95 Ra
Temperature	-10° to +40°C
Illuminance	300-400 lux@ 0.5m
Viewing angle	10°-70°
Battery	2xAAA /1.5V Alkaline
Net weight	56 g



BOSSAUTO INNOVA, S.A.
Pol. Ind. Vallcristol C/ Thomas Edison 16,
08430 La Roca del Vallés, Barcelona
t: +34 938 604 923 / f: +34 938 712 336
info@bossauto.com/ www.bossauto.com



CCT	4000K
Dimensions	Ø16x148mm

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.