

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Colour match lamp MULTIMATCH
CÓDE	050132
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona)
PHONE	902 100 667
FAX	902 363 047
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

BOSSAUTO presents a portable lamp designed for work and perfect for the identification of color variable tonalities, for identifying whether the silver pigmentation is thin or thick and equalize the colors. Plus, it is perfect for checking the coverage, looking over the damaged areas of the vehicle, identifying the defects during the painting process, etc.

Colourmatch is the first range of work lights for colour match and detailing in the world. The special LED with high CRI value is for perfect colour recognition. It is perfect for any paint, polish, cleaning or prep-zone operation and is the only colour match work light range in the world. The sturdy Colourmatch products are designed for use in the painting workshop. They are supplied with a replaceable glass lens resistant to all kind of solvents and tolerating daily cleaning. It increases the quality and finish of each operation and reduce the rate of time-consuming and costly re-work.

Multimatch is an outstanding and powerful colour match work light providing 2000 lumen. It can be used both with cable connection and with battery without cable connection depending on the work task in question. This gives you complete flexibility and unlimited application possibilities. 2-step light function provides up to 6 hours battery operating time. The body is made of diecast aluminum which makes it extremely sturdy and shockproof to endure even strong strokes and shocks. At the same time it is dust and waterproof, IP67. The flexible stand makes it possible to position the lamp in the desired angle.

3. MAIN CHARACTERISTICS

Light source	Ultra-high CRI COB LED
Luminous flux	600/2000 lm (step 1/2)
Operating time	3h
Battery	11.1V / 4400mAh Li-ion
Impact protection	IK07
CRI	95 Ra

Temperature	-10° to +40°C
Illuminance	1400/3500 lux@0.5m (step 1/2)
Operating time	6/1.5 (step 1/2)
Cable	5m
Ingress protection	IP67
Net weight	2140 g
CCT	4500K
Dimensions	220x235x75mm

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.