

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

<b>NAME OF THE PRODUCT</b>	BOSS FIX Résine + peroxyde 1 kg
<b>CODE</b>	090062 (1kg) 090065 (Kit)

## 2. DESCRIPTION

Repair resin for the application with glass wool, glass fabric or glass mat. Product particularly relevant to body shops, where large areas on body panels or plastic parts have to be repaired.

## 3. PRODUCT PREPARATION

Colour shade	Yellow
Mixing ratio	100: 1 - 3
Hardener	Hardener P – mix thoroughly!
Pot life	Approx. 10-15 min. / 20° C
Drying time Object Temp. 20° C Object Temp. 60° C	After approx. 30 - 60 minutes further coats of Boss Fix can be applied. The surface could be sanded after approx. 60 min. with sanding paper P 60 to P 80.
VOC-regulation	EC limiting value for the product (cat. B/b): 250 g/l (2007) This product contains max. 0 g/l VOC [ 0 lbs/gal]

## 4. REMARKS

Cleaning of tools: with universal thinner immediately after use. Do not allow to set hard. Changes or additions to cars in some countries have to be legalized by federal offices.

Shelf life of the product closed and properly preserved, 1 year from manufacture. Expiration date indicated on the package.

Marking	VbF	Hazardous materials directive
Boss Fix	n/a	inflammable, Xn harmful, contains styrene
Hardener	n/a	Xi irritating, oxidizing, contains benzoyl-peroxid

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your environment.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.