

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Safety glasses
CODE	100409
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

BOSSAUTO safety glasses against impacts. They can be used in several sectors: automobile, industry, navigation, carpentry. Also suitable for bricklayers, panel beaters, mechanics, etc.

3. FEATURES

Ocular material	Polycarbonate
Frame material	Nylon
In conformity with the standards	EN166:2001
PPE Category	II
Field(s) of use	Protection against high-speed particles – low energy impact

4. LEVELS OF PROTECTION

4.1. Levels of protection offered by the personal protective equipment

Applicable levels:

- EN 166:2001 – Personal eye-protection – Specifications
- EN 167:2001 - Personal eye-protection – Optical test methods
- EN 168:2001 – Personal eye-protection – Non-optical test methods
- EN170:2002 - Personal eye-protection – Ultraviolet filters – Transmittance requirements and recommended use.

The safety glasses (ref. 100409) is in conformity with the basic and with the following additional requirements provided by the standard(s) of reference for the particular fields of utilization the device is addressed to: EN166:2001 (Protection against high-speed particles – low energy impact).

5. MARKING ELEMENTS ON THE OCULARS

Variación	Ocular 1	Ocular 2
Scale number	-	-
Optical class	1	-
Standard of reference		
Symbol of mechanical resistance	F	-
CE Marking	CE	

6. MARKING ELEMENTS REPRODUCED ON THE FRAME ARE THE FOLLOWING

Standard of reference	EN 166
Protection against high-speed particles – low energy impact	F
CE Marking	CE

Marking position: on the right temple, inner position.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.