

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

<b>NAME OF THE PRODUCT</b>	SEALPLAST brushable sealer grey 1 kg
<b>CODE</b>	070010
<b>DISTRIBUTOR</b>	BOSSAUTO INNOVA, S.A.
<b>ADDRESS</b>	c/ Thomas Edison 16, Apartado de correos 95
<b>CITY</b>	08430 La Roca del Vallés (Barcelona) SPAIN
<b>PHONE</b>	+ 34 93 860 49 23
<b>FAX</b>	+34 93 871 23 36
<b>E-MAIL</b>	<a href="mailto:info@bossauto.com">info@bossauto.com</a>
<b>WEB</b>	<a href="http://www.bossauto.com">www.bossauto.com</a>




## 2. DESCRIPTION

Sealplast Brushable sealer is one-component for use in car refinishing, for the sealing of all bodywork joints, boots, wheel arches...It has excellent sealing characteristics as well as being very resistant to torsion, waterproofing and vibrations. All these characteristics remain lifetime uncharged. Thanks to its low VOC content and the high quantity of binder used, guarantee and excellent adhesion on any kind of supporting surfaces and a very high cohesion, and even in thick applications, the paint will not crack. This product can be over painted after 20-30 minutes with any kind of bodywork paint.

## 3. PHYSICAL CHARACTERISTICS

Nature	Elastomers and synthetic resins
Colour	Grey
Specific weight	1.1kg/l at 20°C
Elongation at break	240-250g/l
VOC	200%

## 4. APPLICATION METHOD

		
		20'-30'

## 5. REMARKS

Clean and degrease the part to be treated. Brush on with smooth continuous strokes, always in the same direction. Do not re-touch more than 2 minutes after application.

## **6. EQUIPMENT CLEANING**

---

Clean the brush with a cleaning thinner before the product hardens.

## **7. SAFETY**

---

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at work and waste Disposal.

## **8. STORAGE**

---

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

## **9. GUARANTEE**

---

In unopened original packaging, one year from manufacturing date.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.