

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	CERATEX 2000 Cavity wax in brown 1L
CODE	070023
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

CERATEX 2000 is specially designed for the protection of bodywork empty spaces such as underbodies, interior doors, wings.... It forms a protector film, it is water repellent, flexible and adherent in a wide range of temperatures. It offers good resistance to abrasion, humidity and detergents usually used in industry. The solvent used in the formulation of this wax does not attack the support of paint.

3. PHYSICAL CHARACTERISTICS

Nature	Waxes and antioxidants
Colour	Beige translucent
Specific weight	0,9kg/l at 20°C
Solid content	42%
VOC	522g/l - 2004/42/EC - IIB(e)(840)(522)

4. APPLICATION METHOD

			
Shake before use	RB1	3-4 kg/cm ²	1

5. REMARKS

Shake before use. Apply the product with extendable tubes for difficult to access areas.

6. EQUIPAMENT CLEANING

Clean with a cleaning thinner.

7. SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at work and waste disposal.

8. STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

9. GUARANTEE

In unopened original packaging, one year from manufacturing date.