

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	CERATEX 20000 Cavity wax spray in white 500 ml
CODE	110063
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. PROPERTIES

CERATEX 20000 Cavity wax spray is specially designed as an inside-protection for cars. The film provides excellent resistant to common road conditions, salt, moisture and general corrosive atmosphere. It should be applied to the inside of box panels, headlight wells, tail light wells, etc. After application a film is formed with a film thickness of 20-40 micron. The product can also be used for rust protection of metal plates.

3. APPLICATION

The surface must be clean, dry and free of grease. Shake before use. Apply the product with adequate homeliness, with normal nozzle or with anti-gravilla gun. Do not apply on the motor, on brakes or exhaust pipe.

4. ELIMINATION

BOSSAUTO spray cavity wax white can be removed by means of mineral spirits.

5. SPECIFICATIONS

Color	White	
Solids	11-12%	DIN 53215
Flash point	<20°C	ASTM D 1320-67
Viscosity	-	
Density	0.679 Kg./L	DIN 51757
Drying time	3-4 hours	
Salt spray test	>500 hours	SS DIN 53210
Copper corrosion	1B	

The technical information is agreed with our experience. We give safety of the product; however, not found the use conditions in our control, we can not assume any responsibility of the obtained results.