

BOSSAUTO INNOVA, S.A.
Pol. Ind. Valldoriolf C' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/www.bossauto.com/



## TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	Paper/wax paper 44 x 54 cm
CODE	040207
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

## 2. DESCRIPTION

Weight (ISO-536)	70±1 g/m²
Whiteness (UNE-57-005/ISO -2470-1977)	>74
Paper relative Humidity (UNE-57-005/ISO-1924-1-1983)	>5%
Minimum Longitudinal Strength (UNE-57-030/ISO-287-1983)	2650m
Minimum Longitudinal Strength in grams	2750g
Minimum cross-resistance (UNE-57-030/ISO-287-1983)	1400m
Minimum cross-resistance in grams	1450g
COBB	<18
Roughness Bendtsen	<200ml/min.
Porosity Bendtsen	<800ml/min.

The above mentioned standards are average values and no granted assurance of specials properties.

The technical information is given in good faith, but the user should assure himself that the performance of the product is sufficient for this application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Bossauto Innova cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for own applications.

1-1