

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

<b>NAME OF THE PRODUCT</b>	Steering wheel protector roll 150 m x 12,5 cm + applicator
<b>CODE</b>	040208
<b>DISTRIBUTOR</b>	BOSSAUTO INNOVA, S.A.
<b>ADDRESS</b>	c/ Thomas Edison 16, Apartado de correos 95
<b>CITY</b>	08430 La Roca del Vallés (Barcelona) SPAIN
<b>PHONE</b>	+ 34 93 860 49 23
<b>FAX</b>	+34 93 871 23 36
<b>E-MAIL</b>	<a href="mailto:info@bossauto.com">info@bossauto.com</a>
<b>WEB</b>	<a href="http://www.bossauto.com">www.bossauto.com</a>

## 2. PROPERTIES

	MEASURING UNIT	VALUE	MEASURING METHOD
Density	g/cm <sup>3</sup>	0.95	DIN EN 1183
Thickness	µm	As ordered	GPA
Tensile strength machine direction	N/mm <sup>2</sup>	70	ASTM D882
Tensile Strength transverse direction	N/mm <sup>2</sup>	28	ASTM D882
Elongation at break machine direction	%	422	ASTM D882
Elongation at break Transverse direction	%	893	ASTM D882
Dart drop	g/ µm	3,45	ASTM 1709-91

The above mentioned standards are average values and no granted assurance of specials properties.