

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf (7 Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



# TECHNICAL DATA SHEET

## **1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY**

NAME OF THE PRODUCT	Dent Away repair KIT
CODE	050024
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

## 2. DESCRIPTION AND KIT CONTENT

Kit for quick repair of surface dents without any need to disassemble the upholstery. The kit contains:

- 2 types of glue: a stronger and resistant one (yellow bar) and a softer (bar transparent).
- 1 triangular adapter.
- 1 rectangular adapter.
- 1 round adapter.
- 1 glue to melt the glue.
- 10 pullers to pull off the glue: 5 of 1.5cm and 5 of 1cm.
- 1 grinding bar.
- 3 adapter threads.
- Adapters with thread (male) of different sizes: 5 conical, 1 rectangular and 4 flat.
- Liquid to disengage the glue.

#### **3. DIRECTIONS OF USE FOR THE GUN**

Glue gun with trigger

- 1. Cleaning de surface to be treated.
- 2. Plug in the gun. Chose the right glue.
- 3. Introduce the glue bar in the rear side of the gun.
- 4. Let it heat for 5 minutes.
- 5. Pull the trigger until the glue comes out of the nozzle.
- 6. There is no need to spread the glue. Press the surface for 15 minutes. There is no need to use clamps or any other fixing devices.
- 7. Do not pull off the glue bar from the gun.
- 8. When finished, unplug the glue gun.



BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf O' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



### 4. SAFETY PRECAUTIONS

- 1. DO NOT TOUCH the nozzle or the melted glue. Temperature can reach 195°C.
- 2. In case of accidental contact with the glue, do not take the glue off. Introduce the burn area into cold water.
- 3. Keep out of reach of children.
- 4. Use safety glasses.
- 5. Do not use outdoors.

#### 5. WARNING

The quality of glue bars s can change depending of the manufacturer concerning its tackiness. In order to achieve the best junctions use #725 strong glue bars.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.