

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf O' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona

t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com/



TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE Lid for 5500 ml mixing cup

PRODUCT

CODE 100299

DISTRIBUTOR BOSSAUTO INNOVA, S.A.

ADDRESS c/ Thomas Edison 16, Apartado de correos 95

CITY 08430 La Roca del Vallés (Barcelona) SPAIN

PHONE + 34 93 860 49 23

FAX +34 93 871 23 36

E-MAIL <u>info@bossauto.com</u>

WEB www.bossauto.com

2. DIMENSIONS

Shape: Round

Volume under lid: 223,8mm+/-2mm

Height: 13,7mm+/-0,2mm

3. LID TYPE

Closure type: Flex-off Lid type: Standard

4. RAW MATERIAL

A. Raw material options

Dry Offset, Optional IML

B. Approvals

All products comply with the FDA and European legislation in force relating to materials and articles intended to come into contact with food.

5. WEIGHT

Weight: 39g +/-4g.

7. PERFORMANCE

A. Hot filling

85-95°C. The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures



BOSSAUTO INNOVA, S.A.
Pol. Ind. Valldorioff O' Thomas Edison 16,

08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



and care must be taken in relation to stacking immediately after hot filling. After cooling of the product and pail, the pail regains its original stacking strength.

B. Cold temperatures

The standard resin material for white/coloured products resists temperatures down to -20°C. Deep freezing below -20° C may require a special resin available on request. Standard transparent (CLX) products might become brittle at temperatures below 0° C.

C. Shelf life

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

D. Quality information

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) on a rolling 12 months basis are considered acceptable in the industry and Therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

8. OTHER

UN approval: No

Special:

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.