

# TECHNICAL DATA SHEET

## 1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

---

<b>NAME OF THE PRODUCT</b>	Lid for calibrated mixing cup 385 ml TechCup
<b>CODE</b>	100334
<b>DISTRIBUTOR</b>	BOSSAUTO INNOVA, S.A.
<b>ADDRESS</b>	c/ Thomas Edison 16, Apartado de correos 95
<b>CITY</b>	08430 La Roca del Vallés (Barcelona) SPAIN
<b>PHONE</b>	+ 34 93 860 49 23
<b>FAX</b>	+34 93 871 23 36
<b>E-MAIL</b>	<a href="mailto:info@bossauto.com">info@bossauto.com</a>
<b>WEB</b>	<a href="http://www.bossauto.com">www.bossauto.com</a>

## 2. DESCRIPTION

---

Lid for calibrated mixing cup 385 ml TechCup. Standard-type lid with snap-on hermetic sealing. Suitable for use in a microwave.

## 3. ROW MATERIAL

---

Row material options: PP

Approvals: All products comply with the FDA and European Legislation in force relating to materials and articles intended to come into contact with food.

## 4. PERFORMANCE

---

### A. Hot filling

85-95°C

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. After cooling of the product and pail, the pail regains its original stacking strength.

### B. Cold temperatures

The standard resin material resists temperatures down to -20°C. Standard transparent products might become brittle at temperatures below 0° C.

### C. Shelf life

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage.



**BOSSAUTO INNOVA, S.A.**  
Pol. Ind. Vallgorriol / Thomas Edison 16,  
08430 La Roca del Vallés, Barcelona  
t: +34 938 604 923 / f: +34 938 712 336  
info@bossauto.com / [www.bossauto.com](http://www.bossauto.com)



#### **D. Quality information**

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) on a rolling 12 months basis are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.