

BOSSAUTO INNOVA, S.A.U. Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 atencioncliente@bossauto.com/ www.bossauto.com



TECHNICAL DATA SHEET

Updating Date: 14/11/2023 Version: 1 (**)Indicates changes from the previous version

SECTION 1. IDENTIFICATION OF THE PRODUCT

1.1 Product identifier:

Other forms of identification:

FLEXIBLE Disc 15 holes 150mm. 060965; 060966; 060967; 060968, 060969.

1.2 Details of the supplier of the technical data sheet: (See FDT headline).

1.3 Emergency telephone: 93 860 49 23 (8:00 - 17:30).

SECTION 2. DESCRIPTION

FLEXIBLE discs are abrasives on flexible film backing specially recommended for use with Interface Micro Vel., as well as hand pads or orbital sanders. FLEXIBLE discs are perfectly bonded by means of Vel.

Designed mainly for use on plastic surfaces for perfect sanding, choose the grain of FLEXIBLE discs that best suits the needs or the stage of the sanding job.

Advantages include:

- High cutting performance without clogging.
- Recommended for sanding curved surfaces.
- Avoids overly aggressive grinding.
- Homogeneous end result.

Reference	Available grains	Colour
060965	P400 ~ P600	Blue
060966	P800 ~ P1000	Yellow
060967	P1200 ~ P1500	Orange
060968	P2000	Lime
060969	P3000	Grey

SECTION 3. TECHNICAL DATA

Adhesive:	Resin on resin.	
Support:	Flexible film.	
Coating:	Aluminium oxide.	
Width:	1020mm.	

The technical information is based on our experience. We guarantee the quality of the product; however, as the conditions of use are not under our control, we cannot assume any responsibility for the results obtained.