

BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf O' Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

NAME OF THE PRODUCT	URAX FILM ø75 mm (50u box)
CODE	060210 to 060217 (P400 to P2000)
DISTRIBUTOR	BOSSAUTO INNOVA, S.A.
ADDRESS	c/ Thomas Edison 16, Apartado de correos 95
CITY	08430 La Roca del Vallés (Barcelona) SPAIN
PHONE	+ 34 93 860 49 23
FAX	+34 93 871 23 36
E-MAIL	info@bossauto.com
WEB	www.bossauto.com

2. DESCRIPTION

URAX FILM discs provide a high performance, durability and resistance during the sanding processes compared with other formats, for dry and wet sanding applications, getting a perfect result.

Grains available:	
060209 - P360	060214 - P1000
060210 - P400	060215 - P1200
060211 – P500	060216 - P1500
060212 - P600	060217 – P2000
060213 - P800	

3. FEATURES AND BENEFITS

- Film is much more durable than paper and will not tear easily. The high durability _ provides longer product life and even surface provides outstanding finish. Film is the best choice for dry and wet sanding applications.
- Bossauto's Film abrasives are made with premium Grit, strong resin bond and special stearated coating. This provides superior performance and life.
- Bossauto's Film abrasives premium Grit and strong resin bond provide faster and sharper cutting performance and longer life than competitors' products.
- Excellent durability: Film backing is very strong and durable. It does not tear easily during sanding operation and is great for edges, corners and irregular shapes.
- Perfect sanding surface: With uniform mineral coating on perfectly even surface, Film works better than paper. The result is outstanding finish without deep scratch marks.



BOSSAUTO INNOVA, S.A. Pol. Ind. Valldoriolf C/ Thomas Edison 16, 08430 La Roca del Vallés. Barcelona t: +34 938 604 923 / f: +34 938 712 336 info@bossauto.com/ www.bossauto.com



The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.