

TECHNICAL DATA SHEET

1. IDENTIFICATION OF THE PRODUCT

NAME OF THE PRODUCT GENIO B5 Fine ceramic fuchsia polish 1 L
CODE 100805

2. DESCRIPTION AND PROPERTIES

GENIO B5 can be used to treat painted surfaces with small, medium or deep defects. Apply by machine or hand. Excellent in old or fresh paint. Use with a foamed lamb's wool pad or hard foam pad. For a high gloss finish use the white foam pad.

- Fast polishing
- High gloss finish
- Leaves absolutely no greasy haze or streaks
- Low product consumption
- Saves application time and material
- Silicone & silica free
- 2 in 1 removes sanding marks and polishes at the same time

3. HEALTH AND SAFETY

Not irritant, not harmful, not flammable.

4. USAGE AND APPLICATION

Liquid abrasive compound for removing painting defects, such as sanding marks, car wash scratches, paint oxidation, etc. Restores shine to opaque and oxidised paint finishes simply. Specially designed and developed for quick and clean use without water. It lets you see the removal of the flaw immediately. Reduced working time. Removes scratches permanently, does not hide imperfections with cosmetic oil. The product works without leaving greasy surface haze which doesn't let you see that the scratch has been removed. It can be used in aluminum.

Ammoniac and silicone free. Paintable. Very low VOC content for a better environmental conditions. For a better result: use with foamed wood pad with low speed 1200-1800rpm approx. for better cutting action. Use with variable contact white foam pad with low speed 1200-1800rpm approx. for a better high glossy result.

1. Apply Genio B5 in small quantities to paint surfaces to be polished. Only polish small areas at a time.
2. Polish the surface applying medium pressure until the scratches and imperfections have been removed.
3. Reduce pressure to allow the pad to polish.
4. After polishing remove any residue and buff the surface with our clean microfibre cloth.
5. In the case of willing to give an extra shine and protection apply B69

A. Notes

- Do not use excessive compound.
- On fresh, sensitive, or paints not completely reticulated, the addition of water can reduce heat build-up from pad friction due to polishing. Avoid excessive quantities of water.
- Once a new pad is activated with water, no additional water is needed during polishing.

5. FEATURES

Composition	Emulsion containing inert inorganic abrasive
Appearance	Liquid compound
Colour	Fuchsia/Black
ODOUR	CHaracteristic
Ph	-
FP	-
VOC	-
Solubility	Miscible in water
Shelf life	18 months closed containers in ambient temperature in sealed container. Protect from frost.
Packing	1L, plastic bottles

The technical information is in accordance with our experience. We assure the quality of the product. However, the conditions of use are not under our control and we cannot assume any responsibility of the obtained results.